

Exhibit C

FEB 16 2006



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re patent application of)	
)	Before the Examiner
Bruce B. Brandt et al.)	
)	Lisa Nhung Klaus
Serial No. 09/714,367)	
)	Group Art Unit 2832
Filed November 16, 2000)	
)	
MULTI-FUNCTION STALK SWITCH)	July 19, 2002

REQUEST FOR EXTENSION OF TIME

Commissioner for Patents
Washington, D.C. 20231

Sir:

Applicants' attorney requests that the date for responding to the Office Action mailed January 25, 2002 for the above-referenced patent application be extended two months to and including July 25, 2002. Applicants previously filed a two-month extension of time on May 29, 2002, and enclosed therewith a fee of \$400.00. Therefore, the Commissioner is hereby authorized to charge the remaining large entity statutory fee of \$520.00 for the third month extension request to the Deposit Account No. 23-3030. No additional fees are believed to be necessary, however, should any fees be deemed required, the Commissioner is authorized to charge such fees to Deposit Account No. 23-3030, but not to include payment of issue fees.

Respectfully submitted

I hereby certify that this paper is being facsimile transmitted to the Lisa Nhung Klaus at Patent and Trademark Office at (703) 746-4148 on the date shown below.

Troy J. Cole

Print name of person signing certification

Signature

July 19, 2002

Date of Signature

By:

Troy J. Cole

Reg. No. 35,102

Woodard, Emhardt, Naughton,

Moriarty & McNett

Bank One Center/Tower

111 Monument Circle, Suite 3700

Indianapolis, Indiana 46204-5137

(317) 634-3456

FEB 16 2006



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re patent application of)	
)	Before the Examiner
Bruce B. Brandt et al.)	
)	Lisa Nhung Klaus
Serial No. 09/714,367)	
)	Group Art Unit 2832
Filed November 16, 2000)	
)	
MULTI-FUNCTION STALK SWITCH)	July 19, 2002

SUPPLEMENTAL RESPONSE TO FIRST OFFICE ACTION

Commissioner for Patents
Washington, D.C. 20231

Sir:

Applicants respectfully request that the prior response submitted May 29, 2002 be withdrawn and that the following response be entered.

In response to the Office Action dated January 25, 2002, please amend the above-identified application as follows:

IN THE DESCRIPTION:

Please replace the paragraph beginning on page 19, line 14, and ending on page 20, line 13, with the following paragraph:

In certain of these alternative embodiments the spring 34A is omitted, the series of female detents 22A is perpendicular to the longitudinal axis 24A of the stalk switch 140 and is radially symmetric about it, and a second spring 340 and a first detent washer

I hereby certify that this paper is being facsimile transmitted to the Lisa Nhung Klaus at Patent and Trademark Office at (703) 746-4148 on the date shown below.	
<u>Troy J. Cole</u>	
Print name of person signing certification	
<u>[Signature]</u>	
Signature	
<u>July 19, 2002</u>	
Date of Signature	

FEB 16 2006

210 are placed inside the first rotary switch module 12A, with the second spring 340 positioned between the first rotary switch module 12A and the first detent washer 210 such that the first detent washer 210 is biased away from the rotary switch module 12A. The first detent washer 210 preferably has a first non-circular outer perimeter 211 shaped to mate with the first rotary switch module 12A, including the male detent 20A, thereby fixing the angular positions of the first detent washer 210 and the first rotary switch module 12A with respect to each other. The first detent washer 210 has a series of small male detents 212 on its distal surface shaped to mate with the series of female detents 22A. When the stalk switch 140 is assembled, the second spring 340 biases the first detent washer 210 and the rotary switch support member 14A together, with the series of small male detents 212 and the series of female detents 22A interfacing, so as to create a counter-torque against any torque applied to the first rotary switch module 12A. The magnitude of the counter-torque is limited by the strength of the second spring 340, and by the shape of the series of small male detents 212 and the series of female detents 22A, so that when sufficient torque is applied to the first rotary switch module 12A, the second spring 340 will compress in order to allow the detents 212 and 22A to slip relative to one another, permitting the first rotary switch module 12A to rotate. When the torque applied is sufficiently reduced, the first rotary switch module 12A will come to rest at one of a finite number of angular positions relative to the rotary switch support member 14A, defined by the series of female detents 22A and the series of small male detents 212.

Please replace the paragraph beginning on page 22, line 13, and ending on page 23, line 2, with the following paragraph:

Figure 16 illustrates certain features of certain alternative embodiments of a stalk switch 140 according to the present invention. In certain alternative embodiments, the pair of magnets 74 and 76 are replaced with a proximal third magnet 774 and a distal third magnet 776, respectively, contained in a pair of plastic plungers 740, having enlarged heads 741, which are positioned in a pair of holes 745 in the rotation assembly 68A, preferably away from its axis of rotation, with their heads 741 contacting the elongated handle stalk 52A. A fourth spring 748 is preferably placed around the body of each of the plungers 740 and between the heads 741 and the rotation assembly 68A, so that the heads 741 are biased away from the rotation assembly 68A. Rotation assembly 68A also contains a fourth magnet 760, preferably positioned far from its axis of rotation and about half-way between the pair of magnets 774 and 776 along the perimeter of the rotation assembly 68A.

IN THE CLAIMS

Please cancel claims 1-25.

Please amend claims 26 and 28 as follows:

26. A multi-function stalk switch comprising:
- a first rotary switch module having a first surface;
 - a rotary switch support member having a second surface;
 - at least one first detent formed on one of said first and second surfaces;

FEB 16 2006

a first detent washer shaped to engage said at least one first detent, and having an angular position fixed relative to one of the first rotary switch module and the rotary switch support member;

a first spring positioned to bias said first detent washer against said at least one first detent;

a second rotary switch module having a third surface;

wherein the rotary switch support member also has a fourth surface;

at least one second detent formed on one of said third and fourth surfaces;

a second detent washer shaped to engage said at least one second detent, and having an angular position fixed relative to one of the second rotary switch module and the rotary switch support member;

a second spring positioned to bias said second detent washer against said at least one second detent.

28. The multi-function stalk switch of claim 26, further comprising:

a handle stalk having a proximal end and a distal end, said proximal end being operatively coupled to said rotary switch support member;

a plunger coupled to said stalk distal end such that said plunger may move linearly with respect to said stalk distal end, said plunger being biased in said distal direction;

a rotational receptacle coupled to said handle stalk such that said handle stalk may pivot in at least one plane; and

a concave centering mechanism having a concave surface and coupled to said rotational receptacle such that said plunger is in contact with said concave surface;

wherein a pivoting force applied to the handle stalk causes said plunger to be displaced along said concave surface, thereby compressing said plunger away from said distal end; and

wherein removal of said pivoting force allows distal linear movement of said plunger in response to said plunger bias, thereby forcing said plunger to a center of said concave surface.

REMARKS

Claims 1-35 are pending in the application. Claims 1-25 have been rejected by the Examiner and claims 26-34 have been objected to. Claim 35 has been allowed. Claims 26 and 28 have been amended herein. Applicants respectfully traverse each ground of rejection and request reconsideration and further examination of the application under 37 CFR § 1.111. Applicants respond to each ground of rejection and objection as follows.

A. Allowable subject matter.

Applicants would like to thank the Examiner for indicating the allowable subject matter of claims 26-35.

B. The disclosure was objected to because of noted informalities.

It is respectfully submitted that pages 20 and 22 of the specification have been amended in order to cure the informalities noted by the Examiner. It is therefore respectfully submitted that the specification is no longer objectionable.

FEB 16 2006

- C. Claims 1-24 were rejected under 35 U.S.C. § 101 as claiming the same invention as that of claims 1-24 of prior U.S. Patent No. 6,020,563.**

It is respectfully submitted that claims 1-24 have been cancelled herein, therefore their rejection under 35 U.S.C. § 101 is now considered moot.

- D. Claims 1-24 were rejected under 35 U.S.C. § 102(b) as being clearly anticipated by Risk, Jr. et al. (U.S. 6,020,563).**

It is respectfully submitted that claims 1-24 have been cancelled herein, therefore their rejection under 35 U.S.C. § 101 is now considered moot.

- E. Claim 25 was rejected under 35 U.S.C. § 102(b) as being anticipated by Dzung et al. (U.S. 5,153,391).**

It is respectfully submitted that claim 25 has been cancelled herein, therefore its rejection under 35 U.S.C. § 102(b) is now considered moot.

For the foregoing reasons, Applicant respectfully submits that the present application is in condition for allowance, and respectfully requests such action. Should it facilitate allowance of the application, the Examiner is invited to telephone the undersigned attorney.

Attached hereto are three pages which present a marked up version of the changes made to this application by the current amendment. This attached page is captioned “VERSION WITH MARKINGS TO SHOW CHANGES MADE.”

Applicants previously filed a two-month Request for Extension of time on May 29, 2002 and included a check for \$400.00 therewith to cover the statutory fees. Therefore, Applicants enclose a check in the remaining amount of \$520.00 for the third month of extension for this response. No additional fees are believed to be necessary,

however, should any fees be deemed required, please charge such fees to Deposit

Account No. 23-3030, but not to include any payment of issue fees.

Respectfully submitted,

By: _____



Troy J. Cole

Reg. No. 35,102

Woodard, Emhardt, Naughton,

Moriarty & McNett

Bank One Center/Tower

111 Monument Circle, Suite 3700

Indianapolis, Indiana 46204-5137

(317) 634-3456

FEB 16 2006

VERSION WITH MARKINGS TO SHOW CHANGES MADE

In the specification:

The paragraph beginning at page 19, line 14 has been amended as follows:

In certain of these alternative embodiments the spring 34A is omitted, the series of female detents 22A is perpendicular to the longitudinal axis 24A of the stalk switch 140 and is radially symmetric about it, and a second spring 340 and a first detent washer 210 are placed inside the first rotary switch module 12A, with the second spring 340 positioned between the first rotary switch module 12A and the first detent washer 210 such that the first detent washer 210 is biased away from the rotary switch module 12A. The first detent washer 210 preferably has a first non-circular outer perimeter 211 shaped to mate with the first rotary switch module 12A, including the male detent 20A, thereby fixing the angular positions of the first detent washer 210 and the first rotary switch module 12A with respect to each other. The first detent washer 210 has a series of small male detents 212 on its distal surface shaped to mate with the series of female detents 22A. When the stalk switch 140 is assembled, the second spring 340 biases the first detent washer 210 and the rotary switch support member 14A together, with the series of small male detents 212 and the series of female detents 22A interfacing, so as to create a counter-torque against any torque applied to the first rotary switch module 12A. The magnitude of the counter-torque is limited by the strength of the second spring 340, and by the shape of the series of small male detents 212 and the series of female detents 22A, so that when sufficient torque is applied to the first rotary switch module 12A, the second spring [34A] 340 will compress in order to allow the detents 212 and 22A to slip relative to one another, permitting the first rotary switch module 12A to rotate. When the torque

FEB 16 2006

applied is sufficiently reduced, the first rotary switch module 12A will come to rest at one of a finite number of angular positions relative to the rotary switch support member 14A, defined by the series of female detents 22A and the series of small male detents 212.

The paragraph beginning at page 22, line 13 has been amended as follows:

Figure 16 illustrates certain features of certain alternative embodiments of a stalk switch 140 according to the present invention. In certain alternative embodiments, the pair of magnets 74 and 76 are replaced with a proximal third magnet 774 and a distal third magnet 776, respectively, contained in a pair of plastic plungers 740, having enlarged heads 741, which are positioned in a pair of holes 745 in the rotation assembly 68A, preferably away from its axis of rotation, with their heads 741 contacting the elongated handle stalk 52A. A fourth spring 748 is preferably placed around the body of each of the plungers [741] 740 and between the heads 741 and the rotation assembly 68A, so that the heads 741 are biased away from the rotation assembly 68A. Rotation assembly 68A also contains a fourth magnet 760, preferably positioned far from its axis of rotation and about half-way between the pair of magnets 774 and 776 along the perimeter of the rotation assembly 68A.

In the claims:

Claims 26 and 28 have been amended as follows:

26. (Amended) [The] A multi-function stalk switch [of claim 25, further] comprising:

a first rotary switch module having a first surface;

a rotary switch support member having a second surface;
at least one first detent formed on one of said first and second surfaces;
a first detent washer shaped to engage said at least one first detent, and having an
angular position fixed relative to one of the first rotary switch module and the rotary
switch support member;
a first spring positioned to bias said first detent washer against said at least one
first detent;
a second rotary switch module having a third surface;
wherein the rotary switch support member also has a fourth surface;
at least one second detent formed on one of said third and fourth surfaces;
a second detent washer shaped to engage said at least one second detent, and
having an angular position fixed relative to one of the second rotary switch module and
the rotary switch support member;
a second spring positioned to bias said second detent washer against said at least
one second detent.

28. The multi-function stalk switch of claim [27] 26, further comprising:
a handle stalk having a proximal end and a distal end, said proximal end being
operatively coupled to said rotary switch support member;
a plunger coupled to said stalk distal end such that said plunger may move
linearly with respect to said stalk distal end, said plunger being biased in said distal
direction;

a rotational receptacle coupled to said handle stalk such that said handle stalk may pivot in at least one plane; and

a concave centering mechanism having a concave surface and coupled to said rotational receptacle such that said plunger is in contact with said concave surface;

wherein a pivoting force applied to the handle stalk causes said plunger to be displaced along said concave surface, thereby compressing said plunger away from said distal end; and

wherein removal of said pivoting force allows distal linear movement of said plunger in response to said plunger bias, thereby forcing said plunger to a center of said concave surface.

Send Confirmation Report

Name: WOODARD EMHARDT ET AL

ID: 317 637 7561

19 Jul 02 4:53PM Page 1

Job	Start Time	Usage	Phone Number or ID	Type	Pages	Mode	Status
162	7/19 4:48PM	5'40"	17037464148.....	Send.....	13/13	EC144	Completed.....

Total 5'40" Pages Sent: 13 Pages Printed: 0

WOODARD, EMHARDT, NAUGHTON, MORIARTY & MCNETT PATENT & TRADEMARK ATTORNEYS

FACSIMILE TRANSMITTAL SHEET

TO:	FROM:
Lisa Nhung Klaus	Troy J. Cole
COMPANY:	DATE:
Patent & Trademark Office	July 19, 2002
FAX NUMBER:	TOTAL NO. OF PAGES INCLUDING COVER:
(703) 305-0422	13
PHONE NUMBER:	SENDER'S REFERENCE NUMBER:
(703) 746-4148	1067-242
YOUR REFERENCE:	RE:
Serial No. 09/714,367	Supplemental Office Action Response
Inventor: Brandt et al.	

☐ URGENT ☐ FOR REVIEW ☐ PLEASE COMMENT ☐ PLEASE REPLY ☐ PLEASE RECYCLE

NOTES/COMMENTS:

Attached: Supplemental Response to First Office Action & Request for Extension of Time

I hereby certify that this paper is being
facsimile transmitted to the Patent and
Trademark Office on the date shown
below.

Print name of person signing certification

July 19, 2002
Date of Signature

THIS MESSAGE IS INTENDED ONLY FOR THE ADDRESSEE(S) IDENTIFIED ABOVE.
It may contain privileged, confidential, attorney work product, or trade secret information that is exempt
from disclosure under applicable laws. If you are not the intended recipient, or an employee or agent
responsible for delivering the message to the intended recipient, you are hereby notified that any
discrimination, distribution, or copying of this message is strictly prohibited. If you have received this
facsimile in error, please notify the sender immediately by telephone and return the facsimile (and all copies)
to the sender by mail at the above address. The sender will reimburse you for reasonable expenses incurred.
Thank you.

WOODARD, EMHARDT, NAUGHTON, MORIARTY & MCNETT
BANK ONE CENTER/TOWER
111 MONUMENT CIRCLE, SUITE 3700
INDIANAPOLIS, IN 46204-5137
PHONE: (317) 614-5456
FAX: (317) 637-7561

552 16 2006

**WOODARD, EMHARDT, NAUGHTON,
MORIARTY & MCNETT**
PATENT & TRADEMARK ATTORNEYS

FACSIMILE TRANSMITTAL SHEET

TO: Lisa Nhung Klaus	FROM: Troy J. Cole
COMPANY: Patent & Trademark Office	DATE: July 19, 2002
FAX NUMBER: (703) 305-0422	TOTAL NO. OF PAGES INCLUDING COVER: 13
PHONE NUMBER: (703) 746-4148	SENDER'S REFERENCE NUMBER: 1067-242
YOUR REFERENCE: Serial No. 09/714,367 Inventor: Brandt et al.	RE: Supplemental Office Action Response


☐ URGENT ☐ FOR REVIEW ☐ PLEASE COMMENT ☐ PLEASE REPLY ☐ PLEASE RECYCLE

NOTES/COMMENTS:

Attached: Supplemental Response to First Office Action & Request for Extension of Time

I hereby certify that this paper is being
facsimile transmitted to the Patent and
Trademark Office on the date shown
below.

Print name of person signing certification


Signature

July 19, 2002

Date of Signature

THIS MESSAGE IS INTENDED ONLY FOR THE ADDRESSEE(S) IDENTIFIED ABOVE.

It may contain privileged, confidential, attorney work product, or trade secret information that is exempt from disclosure under applicable laws. If you are not the intended recipient, or an employee or agent responsible for delivering the message to the intended recipient, you are hereby notified that any dissemination, distribution, or copying of this message is strictly prohibited. If you have received this facsimile in error, please notify the sender immediately by telephone and return the facsimile (and all copies) to the sender by mail at the above address. The sender will reimburse you for reasonable expenses incurred. Thank you.

WOODARD, EMHARDT, NAUGHTON, MORIARTY & MCNETT
BANK ONE CENTER/TOWER
111 MONUMENT CIRCLE, SUITE 3700
INDIANAPOLIS, IN 46204-5137
PHONE: (317) 634-3456
FAX: (317) 637-7561

FEB 16 2006